

CADET COM-PAK MAX



The Com-Pak Max warms up living rooms, bedrooms, and other areas. And you've got options—install vertically or horizontally, with two different grille choices to fit any room.

ARCHITECTURAL - ENGINEERING INFORMATION

Fan forced up flow electric air heaters are ETL listed, factory dual field rated 208V/240V. The galvanized wall mounting can for this heater is made from 20-gauge sheet steel with seven electrical knockouts and 34 cubic inches for a wiring compartment. Each complete heater is of unitized construction, attaches to the wall can with a single screw and is self-contained and completely separate from the wall mounting can. Element construction is a coiled nichrome heating wire sealed in a steel sheath with steel fins brazed to the sheath. Heating unit includes a 16-amp rating at 240V, high temperature manual reset limit switch. A two stage centrifugal blower is driven by an impedance protected motor. The motor is totally isolated from the heating chamber. Metal grilles are of one piece, constructed of 22-gauge steel and finished with a powder coat paint system.

TECHNICAL INFORMATION

UL safety standards require the heater to be placed a minimum distance of 6 inches (15.2 cm) from adjacent surfaces and 4-1/2 inches (11.4 cm) from the floor. Cadet recommends a 12-inch clearance from all surfaces for longer and cleaner performance. A 3-foot (91.44 cm) minimum clearance is required for furniture or other objects placed directly in front of the heater. This model is not approved for ceiling installation. Electric wall heaters and thermostats work best when installed on an inside wall. We recommend installing the heater assembly after walls are finished. Heater must be cleaned every six months minimum.

- Enjoy years of reliable use with our sturdiest sealed element
- Rest easy—includes high-temperature safety shutoff feature
- Fit any application with horizontal or vertical installation options
- Durable design built for years of trouble-free use
- Multi-watt options available
- Easy installation



COM-PAK MAX

Grill: 12"W x 9"H x 1"D or 9"W x 12"H x 1"D

Rough-in: 10-1/8"W x 8"H x 4"D or 8"W x 10-1/8"H x 4"D

Heater assemblies require CC or CCSM wall can, grille kit, and may require a thermostat

| PART | MODEL | DESCRIPTION | WATTS | VOLTS | AMPS | BTUS | WT/LBS |
|-------|--------|------------------------------------|------------------------|-------|---------------------|--------------------------|--------|
| 65037 | CM158 | Heater assembly without thermostat | 700/800/1500 | 208 | 3.4/3.8/7.2 | 2390/2730/5120 | 5 |
| 65033 | CM198 | Heater assembly without thermostat | 400/700/1100/1500/1900 | 208 | 1.9/3.4/5.3/7.2/9.1 | 1710/2730/4095/5120/6825 | 4.8 |
| 65034 | CM198T | Heater assembly with thermostat | | | | | 5 |
| 65035 | CM152 | " | 700/800/1500 | 240 | 2.9/3.3/6.3 | 2390/2730/5120 | 4.3 |
| 65036 | CM152T | " | 525/600/1125 | 208 | 2.5/2.9/5.4 | 1790/2045/3840 | 4.5 |
| 65031 | CM192 | " | 400/700/1100/1500/1900 | 240 | 1.7/2.9/4.6/6.3/7.9 | 1365/2390/3755/5120/6485 | 4.3 |
| 65032 | CM192T | " | 300/525/825/1125/1425 | 208 | 1.4/2.5/4.0/5.4/6.9 | 1025/1790/2815/3840/4860 | 4.5 |

WALL HEATER ACCESSORIES (MODEL CM)

| PART | MODEL* | DESCRIPTION | VOLTS | AMPS | LBS/KGS SINGLE MULTI |
|-------------|------------|---|-------------|------|-------------------------|
| 67061/67060 | CC/CC10 | Wall can for model CS, CM, CE, CB or HW, single or 10-pack, galvanized | | | 2.8/1.3 22.5/10.2 |
| 69111 | CCSMW | Surface mount wall can for model CS, CM, CE or HW, single pack | | | 4.4/2.0 |
| 69112 | CCSMA | 9-13/16" W x 12-3/4" H x 4-7/16" D, white, almond or black | | | |
| 69110 | CCSMB | | | | |
| 67079/67081 | CGW/CGW10 | | | | |
| 67075/67080 | CGA/CGA10 | Vertical grille kit for model CS or CM, single or 10-pack, white, almond or black | | | 1.5/0.7 12.3/5.6 |
| 67082/67083 | CGB/CGB10 | | | | |
| 65005/65006 | CMGW/CMGW5 | | | | |
| 65015/65016 | CMGA/CMGA5 | Horizontal grille kit for model CS or CM, without stat, single or 5-pack, white or almond | | | 2.0/0.9 7.5/3.4 |
| 67063 | CTT1W | Built-in thermostat kit for model CS, CM or CST, single | 240/208/120 | 22 | 0.3/0.1 |
| 67064 | CTT2W | or double pole, 40°F to 85°F (4°C to 29°C), white | | | |
| 67065 | CTT1A | Built-in thermostat kit for model CS, CM or CST, single | 240/208/120 | 22 | 0.3/0.1 |
| 67066 | CTT2A | or double pole, 40°F to 85°F (4°C to 29°C), almond | | | |
| 67067 | CTT1P | Built-in tamperproof thermostat kit for model CS, CM or CST, | 240/208/120 | 22 | 0.3/0.1 |
| 67068 | CTT2P | (no knob) single or double pole, 40°F to 85°F (4°C to 29°C) | | | |
| 67105/67100 | CAMW/CAMA | Adapter plate for model CS, CM, CE or CB, 18-1/2" W x 22" H, white or almond | | | 3.4/1.5 |
| 67115/67110 | SAMW/SAMA | Adapter plate for model CS, CM, CE or CB, 12" W x 21-1/4" H, white or almond | | | 2.8/1.3 |

*Suffix W, A or B in model designates color

Note: 5-pack models must be ordered in multiples of 5; 10-pack models in multiples of 10

